


No. DASH	(OHMS) RESISTANCE
251	250
501	500
102	1,000
202	2,000
252	2,500
502	5,000
103	10,000
203	20,000
253	25,000
503	50,000
104	100,000

13. RUNNING TORQUE: 0.6 OUNCE-INCH, MAX.,
12. OUTPUT SMOOTHNESS: 1.0%.
11. LIFE: 5,000,000 REV. AT 40 RPM.
10. DIELECTRIC STRENGTH: 750 VOLTS AC.
9. POWER RATING: 1.0 WATT AT 40°C.
8. OPERATING TEMPERATURE RANGE: -55° TO +105°C.
7. TEMP. COEFFICIENT OF RESISTANCE: 500 PPM/°C.
6. TOTAL MECHANICAL TRAVEL: 360° CONTINUOUS.
5. THEORETICAL ELECTRICAL TRAVEL: 340° ±5°.
4. INDEPENDENT LINEARITY: ±2%.
3. THEORETICAL RESOLUTION: INFINITE.
2. TOTAL RESISTANCE TOLERANCE: ±20%.
1. TOTAL RESISTANCE: SEE CHART. (OTHER VALUES ON REQUEST).



SCHEMATIC AS VIEWED FROM SHAFT END

16. GOLD PLATED TERMINALS.
15. STAINLESS STEEL SHAFT.
14. NICKEL PLATED BRASS BUSHING.